

 Abrir el navegación y en la barra de direcciones colocar la IP del módem, nos solicitará un usuario y contraseña la cual será: Usuario: admin

Contraseña: @m3r!c@m0v!L



 Hacemos clic en la opción de "Wireless" y luego en la parte derecha selecciona "Primary Network", luego colocamos el nombre deseado para la red en la parte de "Network Name (SSID)".

mary Network Primary Network TURBONETT_C390D4 (88:f7:c7:a0:0b:a7) vanced Primary Network Enabled Automatic Security Configuration dging Network Name (SSID) WPS MM AP Isolate Disabled WPA Disabled WPA WPA2 Disabled Device Name WPA2 Disabled TechnicolorAP	dio	Wireless 802.11 Primary Network : This page allows configura	ation of the Primary Wireless Network and its security setting
Primary Network TURBONETT_C390D4 (88:f7:c7:a0:0b:a7) vanced Primary Network Enabled Automatic Security Configuration dging Network Name (SSID) WPS Closed Network Open WPS Config State: Unconfigured M AP Isolate Disabled WPA Disabled WPA: Disabled WPA2 Disabled Device Name WPA2 Disabled TechnicolorAP	mary Network		
dvanced Primary Network Enabled Automatic Security Configuration hidging Network Name (SSID) WPS Image: Closed Network Closed Network Open WPS Config State: Unconfigured MM AP Isolate Disabled WPA Disabled WPA-PSK WPA2 Disabled Device Name WPA2 Disabled TechnicolorAP	cess Control	Primary Network TURBONETT_C390D4 (88:f7:c7:a0	0:0b:a7)
ridging Network Name TURBONETT_C390D4 WPS ▼ (SSID) Closed Network Open ▼ WPS Config State: Unconfigured //MM AP Isolate Disabled ▼ The physical button on the AP will provision wrefess clents using WPA Disabled ▼ WPA-PSK Disabled ▼ WPA-PSK Disabled ▼ Device Name WPA2 Disabled ▼ TechnicolorAP	dvanced	Primary Network Enabled	Automatic Security Configuration
WPA Disabled * WPA WPA2 Disabled * Disabled *	tridaina	Network Name (SSID) TURBONETT_C390D4	WPS T
/MM AP Isolate Disabled ▼ The physical button on the AP will provision writeless clients using WFA WPA Disabled ▼ WFFF Protected Setup (WFS) WPA-PSK Disabled ▼ Device Name WPA2 Disabled ▼ TechnicolorAP	bridging	Closed Network Open	WPS Config State: Unconfigured
WPA Disabled ▼ WFF Protected Setup (WPS) WPA-PSK Disabled ▼ Device Name WPA2 Disabled ▼ TechnicolorAP	WMM	AP Isolate Disabled V	The physical button on the AP will provision wireless clients using W-Fi Protected Setup (WPS)
WPA-PSK Disabled WPA2 Disabled TechnicolorAP		WPA Disabled *	
WPA2 Disabled * TechnicolorAP		WPA-PSK Disabled *	Device Name
		WPA2 Disabled *	TechnicolorAP

 Para colocar la contraseña personalizada, si las opciones de WPA-PSK y WPA2-PSK están deshabilitadas, nos desplazamos hacia abajo de la pantalla y buscamos la siguiente opción "WEP Encryption" la cual vamos a colocar en "Disabled", realizado este paso se nos habilitan las opciones WPA y precedemos a habilitar para colocar la clave deseada.







4. Finalizamos el proceso haciendo clic en "Apply" para guardar los cambios.

Generate WEP Keys
Apply